52mm



Directions: Whilst wearing rubber gloves, run the hot water then sprinkle one capful of plughole freshener down the plughole. Leave it for 1 hour, then flush with more hot water. For a deeper clean follow the instructions above, then using a damp cloth, coat the plughole freshener around the sink, leave for 10 minutes and rinse. Plughole freshener is suitable for use on all materials and septic systems, but may discolour gold plated fittings. Storage: Keep upright at all times.



80mm

DANGER!

Contains: sodium percarbonate, C12-C15 alcohol ethoxylate with 7MEO. eye damage.

Harmful if swallowed. Causes serious

Read label before use. Keep out of reach of children, If medical advice is needed, have product container or label at hand. Wash contaminated skin thoroughly after handling. Wear protective gloves/protective clothing/eye protection/ face protection. JF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists: Get medical advice/ attention. Store in a dry place. Store in a closed container. Contains: ≥ 30% oxygen-based bleaching agents, 5 - < 15% phosphates, < 5% non-ionic surfactants, < 5% perfumes, Contains (R)-p-mentha-1,8-diene, citral.

Lakeland, LA23 1BQ. lakeland.co.uk Made for Lakeland in UK.

LAB/00116/04

cutter 80 x 52mm Bleed 84 x 56mm

No text outside 77 x 49mm