

# HG®

bathroom

## mould spray



from silicone seals, plaster and tile grouts

500 ml e

### HG mould spray

HG "mould spray" immediately destroys fungus and algae in damp places, inside and outside. For cleaning tiled walls (also suitable for marble) and grouting in the bathroom, shower, toilet, kitchen, cellar, basement, sauna, swimming pool, garage, shed etc.. It cleans also facades, balconies, plant boxes, garden ornaments etc. but excluding wood. HG "mould spray" bleaches grey and black mould spots and green algae spots.

**Directions for use:** The product has a bleaching action. If in doubt, first test on an inconspicuous area or a discreet place. Do not remove fungi and algae before using the product. **Remove the cap and replace it with the spray trigger. Turn the nozzle on the front side a quarter.**

Spray the surface from 3 - 5 cm distance and leave it to work for 30 minutes. In case of stubborn stains, spray again and leave to work for another 30 minutes. Clean the sprayed surface with sponge and water. Elastic grouting (for instance silicon paste) must be washed off after 30 minutes and be treated again. **Turn the nozzle a quarter after use (OFF). Remove spray trigger after use, replace cap and store. To prevent clogging of the spray trigger rinse well with warm water after every use. The product may cause stains on some surfaces. Rinse trigger in sink to prevent dripping of the product and avoid splashing.**

For cleaning large surfaces with green deposits, we advise HG "algae and mould remover".

**Dosage:** 500 ml HG "mould spray" is suitable for 2-3 m<sup>2</sup> of wall surfaces, 6-8 m<sup>2</sup> of tile grout.

**Attention:** We recommend you to ventilate well during use and to wear rubber/plastic gloves. Prevent splashing on clothing, (high) gloss paint and laminated blinds. Rinse with water immediately in case of contact with skin, clothing and sensitive surfaces. Avoid contact with metals such as prints on ornamental strips, aluminium and stainless steel. Do not treat coloured surfaces. We do not recommend using this product on arched ceilings. In elastic grouting (for instance silicon paste) sometimes some permanent brown discolouration may occur after use. In badly glazed tiles and old tiles with hairline cracks brown discolouration may occur. This brown colour can possibly be removed with Hypo (Sodium thiosulfate), which can be obtained from your customer service department. Do not reuse the bottle. **Transport and store cool, dark and in an upright position.** • Medical personnel can request the data sheet via +31 (0)36 54 94 777 • The consumer's information sheet can be obtained via [www.HG.eu](http://www.HG.eu)

QUESTIONS ABOUT CLEANING AND MAINTENANCE?  
[www.HG.eu](http://www.HG.eu)



# HG®


bathroom

## mould spray



from silicone seals, plaster and tile grouts

500 ml e



LL20284  
0518600105076 1505

contains a.o.:  
anionic surfactants,  
chlorine-based bleaching agents < 5%



**WARNING H315-** Causes skin irritation. **H319-** Causes serious eye irritation. **H400-** Very toxic to aquatic life. **EUH206-** Warning! Do not use together with other products. May release dangerous gases (chlorine). **P101-** If medical advice is needed, have product container or label at hand. **P102-** Keep out of reach of children. **P264-** Wash hands thoroughly after handling. **P273-** Avoid release to the environment. **P305+P351+P338-** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. **P337+P313-** If eye irritation persists: Get medical advice/attention.

Made in The Netherlands by  
HG International b.v.,  
Damslusweg 70,  
1332 EJ Almere, The Netherlands,  
Tel.: +31 (0)36-5494700